




**Line strainer type 305 PVC-U**  
**With solvent cement spigots metric**

**Model:**

- Protects valves, pumps, etc. from becoming soiled
- Easy dismantling for cleaning the screens
- **Screen perforation need be ordered separately**
- Overall length according to EN 558

| d<br>(mm) | DN<br>(mm) | Size<br>(inch) | PN<br>(bar) | EPDM<br>Code       | SP | Weight<br>(kg) | FKM<br>Code        | SP | Weight<br>(kg) |
|-----------|------------|----------------|-------------|--------------------|----|----------------|--------------------|----|----------------|
| 20        | 15         | ½              | 10          | <b>161 305 300</b> | 1  | 0.101          | <b>161 305 349</b> | 1  | 0.134          |
| 25        | 20         | ¾              | 10          | <b>161 305 350</b> | 1  | 0.141          | <b>161 305 399</b> | 1  | 0.215          |
| 32        | 25         | 1              | 10          | <b>161 305 400</b> | 1  | 0.226          | <b>161 305 449</b> | 1  | 0.257          |
| 40        | 32         | 1 ¼            | 10          | <b>161 305 450</b> | 1  | 0.348          | <b>161 305 499</b> | 1  | 0.386          |
| 50        | 40         | 1 ½            | 10          | <b>161 305 500</b> | 1  | 0.600          | <b>161 305 549</b> | 1  | 0.632          |
| 63        | 50         | 2              | 10          | <b>161 305 550</b> | 1  | 0.985          | <b>161 305 599</b> | 1  | 1.045          |
| 75        | 65         | 2 ½            | 10          | <b>161 305 600</b> | 1  | 1.868          | <b>161 305 649</b> | 1  | 1.871          |
| 90        | 80         | 3              | 10          | <b>161 305 650</b> | 1  | 2.590          | <b>161 305 699</b> | 1  | 2.585          |

| d<br>(mm) | D<br>(mm) | H<br>(mm) | L<br>(mm) | L1<br>(mm) | L2<br>(mm) | closest<br>inch<br>(inch) |
|-----------|-----------|-----------|-----------|------------|------------|---------------------------|
| 20        | 43        | 65        | 124       | 130        | 28         | ½                         |
| 25        | 47        | 76        | 144       | 150        | 37         | ¾                         |
| 32        | 56        | 90        | 154       | 160        | 37         | 1                         |
| 40        | 64        | 104       | 174       | 180        | 44         | 1 ¼                       |
| 50        | 82        | 124       | 194       | 200        | 48         | 1 ½                       |
| 63        | 95        | 148       | 224       | 230        | 60         | 2                         |
| 75        | 106       | 188       | 284       | 290        | 74         | 2 ½                       |
| 90        | 120       | 205       | 300       | 310        | 85         | 3                         |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>