




**Line strainer type 305 PVC-C**  
**With solvent cement spigots metric**

**Model:**

- Protects valves, pumps, etc. from becoming soiled
- Easy dismantling for cleaning the screens
- Overall length EN 558
- Cylindrical screen must be ordered separately

| d<br>(mm) | DN<br>(mm) | PN<br>(bar) | EPDM<br>Code       | SP | Weight<br>(kg) | FKM<br>Code        | SP | Weight<br>(kg) |
|-----------|------------|-------------|--------------------|----|----------------|--------------------|----|----------------|
| 20        | 15         | 10          | <b>163 305 302</b> | 1  | 0.110          | <b>163 305 317</b> | 1  | 0.120          |
| 25        | 20         | 10          | <b>163 305 303</b> | 1  | 0.160          | <b>163 305 318</b> | 1  | 0.160          |
| 32        | 25         | 10          | <b>163 305 304</b> | 1  | 0.250          | <b>163 305 319</b> | 1  | 0.250          |
| 40        | 32         | 10          | <b>163 305 305</b> | 1  | 0.380          | <b>163 305 320</b> | 1  | 0.640          |
| 50        | 40         | 10          | <b>163 305 306</b> | 1  | 0.640          | <b>163 305 321</b> | 1  | 0.640          |
| 63        | 50         | 10          | <b>163 305 307</b> | 1  | 1.072          | <b>163 305 322</b> | 1  | 1.076          |

| d<br>(mm) | D<br>(mm) | H<br>(mm) | L<br>(mm) | L1<br>(mm) | L2<br>(mm) | closest<br>inch<br>(inch) |
|-----------|-----------|-----------|-----------|------------|------------|---------------------------|
| 20        | 43        | 65        | 124       | 130        | 28         | 1 1/2                     |
| 25        | 54        | 76        | 144       | 150        | 37         | 3/4                       |
| 32        | 62        | 90        | 154       | 160        | 37         | 1                         |
| 40        | 71        | 104       | 174       | 180        | 44         | 1 1/4                     |
| 50        | 88        | 124       | 194       | 200        | 48         | 1 1/2                     |
| 63        | 103       | 148       | 224       | 230        | 60         | 2                         |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>