



PROGEF Standard Line strainer type 305 With fusion sockets metric

Model:

- Material: PP-H
- Protects valves, pumps, etc. from becoming soiled
- Easy dismantling for cleaning the screens
- Screen perforation 0.5 mm
- For easy installation and removal
- Overall length according to EN 558

d (mm)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
20	15	10	35	167 305 000	1	0.209	167 305 049	1	0.214
25	20	10	65	167 305 050	1	0.256	167 305 099	1	0.257
32	25	10	90	167 305 100	1	0.329	167 305 149	1	0.327
40	32	10	155	167 305 150	1	0.579	167 305 199	1	0.586
50	40	10	225	167 305 200	1	0.758	167 305 249	1	0.748
63	50	10	370	167 305 250	1	1.188	167 305 299	1	1.185

d (mm)	D (mm)	H (mm)	L (mm)	L2 (mm)	z (mm)	closest inch (inch)
20	52	75	168	130	140	½
25	62	80	192	150	160	¾
32	68	90	206	160	170	1
40	85	110	230	180	190	1 ¼
50	85	125	256	200	210	1 ½
63	102	150	294	230	240	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>