



Backing flange PP-Steel metric For butt fusion systems metric



Model:

- Material: PP (30% glass-fibre reinforced) with steel ring
- Connecting dimension: ISO 7005, EN 1092, BS 4504, DIN 2501
- **Bolt circle PN 10**

AL: number of holes

¹⁾ Suitable for socket -and butt fusion systems

²⁾ Combined version, bolt circle metric - ANSI



	d	D	DN	PN	Code	Weight	D1	D2	D3	H max.	AL	SC
	(mm)	(mm)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)		
1	20	95	15	16	727 700 206	0.216	65	28	14	12	4	M12
1	25	105	20	16	727 700 207	0.279	75	34	14	12	4	M12
1	32	115	25	16	727 700 208	0.429	85	42	14	16	4	M12
1	40	140	32	16	727 700 209	0.621	100	51	18	16	4	M16
1	50	150	40	16	727 700 210	0.722	110	62	18	20	4	M16
1	63	165	50	16	727 700 211	0.900	125	78	18	20	4	M16
1	75	185	65	16	727 700 212	1.110	145	92	18	20	4	M16
	90	200	80	16	727 700 313	1.390	160	108	18	20	8	M16
	110	220	100	16	727 700 314	1.407	180	128	18	20	8	M16
	125	220	100	16	727 700 315	1.408	180	135	18	20	8	M16
	140	250	125	16	727 700 716	2.318	210	158	18	24	8	M16
2	160	285	150	16	727 700 717	3.491	240	178	22	24	8	M20
	180	285	150	16	727 700 718	3.108	240	188	22	24	8	M20
2	200	340	200	16	727 700 719	5.600	295	235	22	27	8	M20
2	225	340	200	16	727 700 720	5.533	295	238	22	27	8	M20
	250	395	250	16	727 700 721	6.632	350	288	22	30	12	M20
	280	395	250	16	727 700 722	6.573	350	294	22	30	12	M20
	315	445	300	16	727 700 723	7.903	400	338	22	34	12	M20
	355	515	350	16	727 700 724	14.587	460	376	23	40	16	M20
	400	574	400	16	727 700 725	20.034	515	430	26	40	16	M24

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>