



ELGEF Plus Pressure tapping valve PE100
d63-250mm / SDR11 / With 360° rotatable outlet

- 10 bar Gas / 16 bar Water
- With integrated drill bit to tap live mains under pressure
- Complete with lower part and premounted PE100 coated valve piece
- The valve is closed clockwise
- Number of turns to fully open or close valve is 13 for outlet d32
- Number of turns to fully open or close valve is 28 for outlet d63
- Spindle size (SW) 14
- 4 mm pin connectors
- Limited path fusion indicators
- Long fusion outlet

d	SDR	PN	DN	d1	Code	Weight
(mm)		(bar)	(mm)	(mm)		(kg)
63	11	16	50	32	193 155 234	1.811
63	11	16	50	63	193 155 237	2.680
75	11	16	65	32	193 155 244	1.943
75	11	16	65	63	193 155 247	2.749
90	11	16	80	32	193 155 254	1.894
90	11	16	80	63	193 155 257	2.781
110	11	16	100	32	193 155 264	1.896
110	11	16	100	63	193 155 267	2.739
125	11	16	100	32	193 155 274	1.986
125	11	16	100	63	193 155 277	2.867
140	11	16	125	32	193 155 284	2.009
140	11	16	125	63	193 155 287	2.908
160	11	16	150	32	193 155 294	2.029
160	11	16	150	63	193 155 297	2.913
180	11	16	150	32	193 155 304	2.111
180	11	16	150	63	193 155 307	2.923
200	11	16	200	32	193 155 314	2.127
200	11	16	200	63	193 155 317	3.007
225	11	16	200	32	193 155 324	2.091
225	11	16	200	63	193 155 327	2.932
250	11	16	250	63	193 155 337	2.978

d2	H	H1	L	L1	z	SDR pipe
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	
21	202	97	165	70	127	9 - 11
31	272	112	165	100	160	9 - 11
21	208	103	165	70	127	9 - 11
31	278	118	165	100	160	9 - 11
21	216	111	165	70	127	9 - 11
31	286	126	165	100	160	9 - 11
21	226	121	182	70	127	9 - 17.6
31	296	136	182	100	160	9 - 17.6
21	233	128	165	70	127	9 - 17.6
31	303	143	165	100	160	9 - 17.6
21	241	136	165	70	127	9 - 17.6
31	311	151	165	100	160	9 - 17.6
21	251	146	182	70	127	9 - 17.6
31	321	161	182	100	160	9 - 17.6
21	261	156	165	70	127	9 - 26
31	331	171	165	100	160	9 - 26
21	271	166	165	70	127	9 - 26
31	341	181	165	100	160	9 - 26
21	281	178	165	70	127	11 - 26
31	353	193	165	100	160	11 - 26
31	366	206	165	100	160	11 - 26

Data sheet

valid from: 9/28/21



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>