


ELGEF Plus Ball valve PE100 d20-225mm / SDR 11



- 10 bar Gas / 16 bar Water
- d160 up to d225 are supplied with base plate and straps
- d1 = diameter of bore
- Regarding pressure rate and application local standards and regulations have to be considered
- * In accordance with ANSI B16.40



d	DN	Code	Weight	d1	L1	H	H1	t
(mm)	(mm)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
20	15	193 103 206	0.487	23	264	144	106	72
25	20	193 103 207	0.490	23	264	144	106	72
32	25	193 103 208	0.506	23	274	144	106	76
40	32	193 103 209	0.616	30	301	152	110	85
50	40	193 103 210	0.829	38	327	166	117	92
63	50	193 103 211	1.174	48	350	174	115	101
75	65	193 103 212	1.434	48	376	183	124	114
90	80	193 103 213	2.918	68	439	249	167	128
110	100	193 103 214	4.416	83	496	276	180	148
125	100	193 103 040	4.220	62	400	280	195	106
160	150	193 103 042	10.541	88	450	360	235	116
180	150	193 103 043	10.524	88	540	360	235	117
200	200	193 103 044	12.023	88	540	360	235	164
*	225	193 103 045	24.400	120	880	470	322	240

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>