




Check valve type 561 PVC-U With solvent cement sockets Inch BS

Model:

- Sealing at a minimum water column of 2 m
- Designed for easy installation and removal
- Vibration free even at high flow velocity
- Flow-optimized return cone, double guided
- For vertical installation
- Compact installation length, same as ball valve type 546
- Z-length, end connectors and union nuts **not** compatible with type 360
- New DN65-DN100



d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
16	10	3/8	16	190	161 561 061	1	0.120	161 561 071	1	0.120
20	15	1/2	16	180	161 561 062	1	0.120	161 561 072	1	0.120
25	20	3/4	16	380	161 561 063	1	0.250	161 561 073	1	0.270
32	25	1	16	460	161 561 064	1	0.276	161 561 074	1	0.280
40	32	1 1/4	16	850	161 561 065	1	0.490	161 561 075	1	0.490
50	40	1 1/2	16	1080	161 561 066	1	0.760	161 561 076	1	0.770
63	50	2	16	1670	161 561 067	1	1.374	161 561 077	1	1.370
75	65	2 1/2	16	2950	161 561 068	1	3.160	161 561 078	1	3.170
90	80	3	16	3600	161 561 069	1	5.070	161 561 079	1	5.090
110	100	4	16	4150	161 561 070	1	8.010	161 561 080	1	8.050

D (mm)	L (mm)	L2 (mm)	z (mm)	closest inch (inch)
50	92	56	60	
50	95	56	60	
58	110	65	69	
68	123	71	75	
84	146	85	89	
97	157	89	97	
124	183	101	110	
166	233	136	144	2 1/2
200	254	141	151	
238	301	164	174	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>